

## DesignMax DM5C in-ceiling loudspeaker

ARCHITECTS' & ENGINEERS' SPECIFICATIONS

OCTOBER 2019

The loudspeaker shall contain a two-way 5.25-inch woofer and 1-inch tweeter coaxially mounted within the Dispersion Alignment system.

The loudspeaker shall meet the following performance specifications: On-axis system frequency response shall be 65 Hz to 20 kHz (-10 dB) with the use of recommended active equalization. The loudspeaker sensitivity shall be 86 dB SPL in half-space environment with Bose EQ voicing with 1 W input at 1 meter. The long-term power handling rating shall be 60 W (AES test methodology using IEC system noise, 2-hour duration). Maximum continuous output shall be 104 dB SPL and the maximum peak output shall be 110 dB SPL, both in half-space environment with Bose EQ voicing. The nominal coverage pattern shall be 160° conical at 1-4 kHz.

The loudspeaker shall be constructed of an engineered-plastics front baffle with a low-profile integrated steel formed enclosure. The loudspeaker shall consist of PC-PBT plastic materials that are resilient to cooking oil exposure. The loudspeaker shall be plenum rated for use in air handling spaces and in compliance with the following safety standards; UL1480A, UL2043. The transducers shall be located behind a perforated steel grille with a powder-coated finish that is magnetically attached. The loudspeaker shall contain a proprietary mounting system including spring-loaded mounting arms. The loudspeaker shall be available in black or white and shall be paintable. Input connectors shall be a Euroblock 6-pin connector with loop-through, located on the front baffle. The loudspeaker shall have a nominal rated impedance of 8 ohms and shall be wired in parallel with a line voltage matching (stepdown) transformer with a level selector appropriate for output taps of 3, 6, 12, 25, 50 Watts and Bypass (8 ohms). The loudspeaker input connections shall allow for direct connection to 70-volt, 100-volt or low-impedance amplifiers. Loudspeaker backcan dimensions shall be 244 x 192 mm (9.6 x 7.6 in) and net weight shall be 4.45 kg (9.6 lbs) with grille. Outward front grille dimensions shall be 304 mm (12.0 in).

Warranty shall be 5 years. The loudspeaker shall be the DesignMax DM5C in-ceiling loudspeaker.